## **NEW PRODUCT SERIES**

**Technical Information Spec-sheet** 





TECHNICAL CHARACTERISTICS				
Available Formats:	4x24			
Style Description:	Stone	Glaze Application Method:	Inkjet	
Visual Characteristics:	Stone	Number of Faces/Screens:	6	
Thickness in mm:	9mm	Number of Punches/Molds:	1	
Modular Suitability:		Body Type:	Ceramic	
Application:	Residential Wall	Color Body Unglazed:	Glazed Normal	
Recycled Content:	40%	Surface Type:	High Relief Glossy	
Post or Pre Customer				
Rectified or Pressed	Pressed	Recommended Grout Joint:	2mm	

PRODUCT TESTING INFORMATION  Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)				
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	No	
Scratch Hardness (MOHS)		Breaking Strength:		
Frost Resistant:	No	Thermal Shock Resistance:		
PEI/Abrasion Resistance:		Deep Abrasion Test	No	
		<175mm <sup>2</sup> :		
Chemical Resistance:				

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.