

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

PACIFIC

TECHNICAL CHARACTERISTICS

| | | | |
|---|----------------------|---------------------------|----------------|
| Available Formats: | 12x24 | | |
| Style Description: | Blue Slate | Glaze Application Method: | Inkjet |
| Visual Characteristics: | Slate | Number of Faces/Screens: | 25 |
| Thickness in mm: | 8.8 | Number of Punches/Molds: | |
| Modular Suitability: | Yes | Body Type: | Porcelain |
| Application: | Residential/Exterior | Color Body Unglazed: | Glazed |
| Recycled Content: Post or Pre Customer | 3% | Surface Type: | Matte/Textured |
| Rectified or Pressed | Pressed | Recommended Grout Joint: | |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|----------|---|----------|
| Water Absorption: | < 0.5% | Static COF: | |
| Shade Variation (1, 2, 3, 4) | V4 | Dynamic COF: | 0.74 |
| Scratch Hardness (MOHS) | 7 | Breaking Strength: | > 1,300N |
| Frost Resistant: | Yes | Thermal Shock Resistance: | passes |
| PEI/Abrasion Resistance: | 3 | Deep Abrasion Test <175mm ² : | |
| Chemical Resistance: | GLA, GHA | | |

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".