



“Oblìo” in a 60x60x2cm (24” x 24”) format recalls a weft of the 60’s, made in two different designs which can be juxtaposed in any way obtaining smoothed cornered rectangles, creating designs that are always different and thus avoiding the unpleasant redundant effect. The surface is finished with three types of textures: partially refined, opaque and polished, all manually achieved by electrical tools having small discs or diamond millers made specifically for the Oblìo. The black limestone becomes black only when it is polished.

As with most Giovanni Barbieri designs, OBLÌO is ideal for high-impact focal points. Color variation is slight however this is a hand finished product which will have some variations in surface presentation.

OBLÌO is made from recycling marble dust production waste, reproducing faithfully the Natural Stone’s beauty. It is suitable for any installation even where Natural Stone is not suggested.

No maintenance. Not absorbent. UV color protection tested by laboratory.

Lead times from Italy can be 7-10 weeks



APPLICATION	CHARACTERISTICS	INSTALLATION/CARE & MAINTENANCE	PACKAGING
<p>Interior & Exterior Residential & Commercial</p> <ul style="list-style-type: none"> - Bathroom - SPA/Wellness Area - Swimming Pool - Building Lobby - Feature Wall - Restaurant/Lounge Bar - Living Room - Reception Hall - Modern Wall - Contemporary Concept - Any Climate Condition interiors exteriors. 	<p>Natural Stone Colour Variation:</p> <ul style="list-style-type: none"> - Very low on all colours: White, Beige Limestone Dark and Light Grey, Light Brown Stones. <p>Surface Variation:</p> <ul style="list-style-type: none"> - It is finished by hand : some difference are normally as related of its Artisan manufacture quality. - Tiles edge are little bevelled. <p>Sizes available:</p> <ul style="list-style-type: none"> - 24"x24"x3/4 - Cm 60x60x2 	<p>Installation:</p> <ul style="list-style-type: none"> - dry layout before installation. - Two components Adhesive. - Pay attention of bottom tile edge during installation. - Tiles joint 0 to 1/8". - sanded grout. <p>Care & Maintenance:</p> <ul style="list-style-type: none"> - No chemicals are applied on Tiles: we recommend this after installation completed referring their destination use. - penetrating sealer (no water effect). - ph neutral cleaner. 	<p>Carton Box on Crate:</p> <ul style="list-style-type: none"> - 2 Tiles per Carton Box - 20 Tile/Boxes per Crate - 10 Pcs Pattern 1 - 10 Pcs Pattern 2 <p>Crate Size: 31" x 45" x H 32" Cm. 78 x 114 x H 80</p> <p>Tiles Weight :</p> <ul style="list-style-type: none"> Kg per SF 4,38 aprox. Kg per SqM 47,00 aprox.